

# Palm Beach Renewable Energy Facility No. 2

## *Solid Waste Authority of Palm Beach County*

*West Palm Beach, Florida, USA*

Babcock & Wilcox (B&W) and its consortium partner, KBR, Inc., engineered, designed, procured and constructed a state-of-the-art waste-to-energy (WTE) power plant for the Solid Waste Authority (SWA) of Palm Beach County in West Palm Beach, Florida.

B&W, through its subsidiary Palm Beach Resource Recovery Corporation (PBRRRC), is also providing operation and maintenance (O&M) services for the new facility. Palm Beach Renewable Energy Facility (PBREF) No. 2 is the first WTE project of its kind in more than 20 years in the United States (U.S.).

B&W and KBR shared the design and build work scope. Commercial operation began in July 2015.

B&W designed and supplied three mass burn Stirling® power boilers capable of generating up to 95 megawatts (MW) gross of electricity, enough to power the equivalent of more than 55,000 homes. In addition to the boilers, B&W provided the combustion grate system, ash systems, metals recovery systems, emissions control equipment, continuous emissions monitoring system (CEMS), automated refuse crane, and other components. KBR provided the balance of plant equipment, detailed engineering and construction services.

The emissions control system consists of spray dryer absorbers (SDA) for acid gas and sulfur dioxide (SO<sub>2</sub>) control, pulse jet fabric filters (PJFF) for particulate control, activated carbon injection to control mercury and dioxins/furans, and a selective catalytic reduction (SCR) system for nitrogen oxides (NO<sub>x</sub>) control.



## PBREF No.2 Details/Specifications

<b>General</b>	
Area Served	Palm Beach County, Florida
Ownership	Solid Waste Authority of Palm Beach County
Construction	Project awarded in 2011; construction started in 2012
Start-up	Commercial operation began July 2015
Operation and Management	Palm Beach Resource Recovery Corporation, a B&W subsidiary
Original O&M Contract	2015 to 2035
<b>Waste Processing System</b>	
MSW Capacity	3000 ton/day 1,000,000 ton/year
Solid Waste Process Lines	3 lines at 1000 ton/day each
<b>Steam/Power Production</b>	
Boilers	3 B&W Stirling® power boilers
Feed System	Automated refuse cranes, charging hopper, damper, water-cooled feed chute, hydraulic ram feeder
Grate Design	B&W Vølund DynaGrate® traveling grate
Primary Fuel	Unprocessed municipal solid waste
Auxiliary Fuel	Natural gas
Steam Capacity	284,400 lb/h (per boiler)
Electric Power Capacity	95 MW gross; powers approximately 55,000 homes
Flyash Removal System	by Allen-Sherman-Hoff (a B&W subsidiary)/Loibl
<b>Environmental Equipment (by B&amp;W)</b>	
Particulates	Pulse jet fabric filters
Acid Gases (primarily sulfur and chlorine)	Spray dryer absorbers (scrubbers)
Nitrogen Oxides (NO <sub>x</sub> )	Selective catalytic reduction (SCR) systems
Mercury	Powdered activated carbon (PAC) injection
Emissions Monitoring	B&W KVB-Enertec™ continuous emissions monitoring system (CEMS)

The facility is capable of processing 3000 tons of municipal solid waste per day to produce electricity and significantly reduce the amount of waste sent to the county's landfill.

The project scope includes the installation of a metals recovery system to maximize the recovery and recycle of aluminum, steel and other metals.

The new plant is located on 24 acres adjacent to the SWA's existing WTE plant, PBREF No. 1, which was also designed and built by B&W. PBRRRC has also operated PBREF No. 1 since it went online in 1989. In 2007, based in part on a successful operating history, SWA selected PBRRRC to provide the O&M services for a second operating term through 2029.

### Process description

Municipal solid waste (MSW), collected from homes and businesses in Palm Beach County, is delivered to transfer stations. Trucks then transport the MSW to the Palm Beach Renewable Energy Park where it is distributed to either PBREF No. 1 or the newly constructed PBREF No. 2. For PBREF No. 2, MSW is unloaded into a large pit located in the refuse building.

Crane operators, housed within the control room, manage the waste deliveries by clearing the area where the trucks drop the waste and removing any large objects which could potentially jam the processing equipment. MSW is delivered to the boilers through charging hoppers and is fed onto B&W Vølund DynaGrate® traveling grates where it is combusted.

The heat generated by the combustion reaction is used to boil water inside the boilers to produce steam. Steam is delivered to the facility's turbine generator where the energy is converted to up to 95 gross MW of electricity that is sold to Florida Power & Light. Flue gases generated by the combustion reaction are then processed by the emissions control system to remove air pollutants.

The emissions control system provided by B&W is designed to remove acid gases, heavy metals, and particulates from the flue gas stream before exiting

the stack. The SCR system is the first to be installed on a WTE power plant in the U.S. The cold-side SCR arrangement utilizes a unique heat recovery system to maximize power production without burning natural gas.


A B&W KVB-Enertec™ continuous emissions monitoring system analyzes the flue gas to determine the concentration of regulated emissions on a continuous basis before the flue gas is sent to the stack.

Bottom and flyash byproducts of the combustion process are delivered, along with any metallic items, to an ash management building via a series of conveying equipment. A rotary magnet removes the ferrous metals and an eddy current separator removes the nonferrous metals from the ash stream

to be recovered for resale on the scrap metal market. The remaining ash is collected in bunkers where it is loaded onto trucks for transporting to a landfill.



A view inside the furnace shows the fuel ram feeder, B&W Vølund DynaGrate® traveling grate combustion system, and weld overlay for lower furnace tube corrosion protection.



Side and plan views of the steam generation and emissions control equipment at PBREF No. 2.



*The state-of-the-art PBREF No. 2 waste-to-energy facility features three B&W boilers and associated emissions control equipment, making it one of the cleanest renewable energy facilities in the United States.*

## **Babcock & Wilcox**

20 South Van Buren Avenue  
Barberton, Ohio, U.S.A. 44203  
Phone: +1 330.753.4511  
Fax: +1 330.860.1886

[www.babcock.com](http://www.babcock.com)     

The information contained herein is provided for general information purposes only and is not intended nor to be construed as a warranty, an offer, or any representation of contractual or other legal responsibility.

*Stirling* and *KVB-Enertec* are trademarks of The Babcock & Wilcox Company.

*DynaGrate* is a trademark of Babcock & Wilcox Vølund A/S.



ENERGY | ENVIRONMENTAL

Established in 1867, Babcock & Wilcox is a global leader in advanced energy and environmental technologies and services for the power and industrial markets, with operations, subsidiaries and joint ventures worldwide.

For more information, or a complete listing of our sales and service offices, send an e-mail to [info@babcock.com](mailto:info@babcock.com), or access our website at [www.babcock.com](http://www.babcock.com).