

# Diamond Power® KilnCam® High-Resolution Camera Featuring TempVu® Technology


The Diamond Power® KilnCam® high-resolution camera, provided by Babcock & Wilcox (B&W), features a two-color temperature measurement for highly accurate readings. The KilnCam camera provides high-resolution images, has no moving parts, and has a variety of mounting configurations that can be incorporated to meet installation requirements.

The KilnCam high-resolution camera can view the product in the burner zone just before it is ready to exit, and provides temperature feedback to the operators so that burner adjustments can be made to meet the optimum material temperature. The camera is mounted on the kiln hood looking into the combustion zone area and provides an important insight for improving product quality.

The Diamond Power exclusive TempVu® software system used with the KilnCam camera has up to 15 user-definable temperature regions, and single- or multi-point region averaging. This allows the user to select multiple regions of interest, and of varying sizes and shapes. The system also features automatic temperature data storage at user-defined intervals to provide historical data for trending or issue analysis. A complete color palette is available for colorizing the monochrome video images, providing the operator with the ability to choose between seeing the monochrome image, or a pseudo-color image which best shows the natural colors in the kiln.

## Benefits

- Accurate temperature readings eliminate the need to know the material emissivity
- Improves product quality
- Less maintenance than conventional cameras
- Longer mean time between failure (MTBF)
- Produces high-resolution digital images
- Reduces the amount of cooling air required
- Wide temperature range
- Provides a variety of mounting configurations
- Unique dual-walled construction isolates and seals the camera against contaminants



The KilnCam® high-resolution camera with TempVu® software system screenshot.

## Features

- Two-color temperature measurement for higher accuracy
- No moving parts
- High resolution 1024 x 768 SVGA images
- High resolution/temperature optical probe
- Temperature range = 1400 to 3000F (760 to 1649C)
- Diamond Power TempVu technology provides:
  - Up to 15 user-definable temperature regions
  - Single- or multi-point region averaging
  - Bitmap image storage
  - Automatic temperature data storage at user-defined intervals
  - Color palette for colorizing the monochrome video image
  - Individual contrast and brightness control
  - Auto-archive of bitmap images
  - Sequential switching of cameras
  - Graphical trending of temperature regions
  - 4 to 20 mA output
- Proprietary HTH-8 high-temperature camera housing
  - Dual-wall construction housing
  - Can use water- or air-cooling

(Continued on reverse side)

## KilnCam® High-Resolution Camera Specifications

Accuracy	±1%
Temperature Measurement Range	1400 to 3000F (760 to 1649C)
Calibration	Factory set
Cooling Requirements	Optical Probe: 3 to 5 psi (20.7 to 34.5 kPa) @ 17 to 22 scfm (0.008 to 0.10 Nm <sup>3</sup> /s) Air-Cooled Housing: 60 to 80 psi (414 to 552 kPa) @ 15 to 20 scfm (0.007 to 0.009 Nm <sup>3</sup> /s)
Data Outputs	Four (4) individual 4 to 20 mA outputs per PC (Optional)
Measurement Field-of-View	60° height x 45° vertical (Entire image area)
Operating Requirements	Camera Assembly: 14 to 200F (-10 to 93.3C) with cooling Optical Probe: up to 3000F (1649C) with cooling Ethernet interface box: 14 to 150F (-10 to 65.6C) (Located within 12 ft from camera)
Power Requirements	Camera site equipment: 100 to 204 VAC, 50/60 Hz @ 1.1 amps maximum
Temperature Measurement Resolution	10F (5.6C) over full image
Temperature Update	≥ 5 seconds
Weight	22 lb (10 kg) for 24 in. optical probe
Data Communication	Cat5E or 6 Ethernet 328 ft (100 m) max. standard. Optional dual LC fiber optic multimode, 50/125 micron, 1640 ft (500 m) max.

### Availability

Contact your local Babcock & Wilcox representative, or call us at (800) 700-2791.

#### Babcock & Wilcox

20 South Van Buren Avenue  
Barberton, Ohio, U.S.A. 44203  
Phone: +1 800.700.2791

[www.babcock.com](http://www.babcock.com)     

The information contained herein is provided for general information purposes only and is not intended nor to be construed as a warranty, an offer, or any representation of contractual or other legal responsibility.

*Diamond Power, KilnCam and TempVu* are trademarks of The Babcock & Wilcox Company.

Babcock & Wilcox supplies Diamond Power controls, electronics, diagnostics and instrumentation.

© 2017 The Babcock & Wilcox Company. All rights reserved.



ENERGY | ENVIRONMENTAL

Established in 1867, Babcock & Wilcox is a global leader in advanced energy and environmental technologies and services for the power, industrial and renewable markets, with operations, subsidiaries and joint ventures worldwide.

For more information or to contact us, visit our website at [www.babcock.com](http://www.babcock.com).